



FLOOR FITTING ACCESSORIES, ADHESIVES AND TOOLS


PROFILES

SOLID T BAR (Threshold Bar)

(900mm, 1800mm or 2700mm with fixing bar)

Where two level surfaces meet, such as wood to wood or wood to tile. Mainly used at internal door thresholds or for a break in the flooring to allow change in direction. covers expansion gap space between two equal height flooring surfaces.

various wood species available.




SOLID L BAR

(900mm, 1800mm or 2700mm with fixing bar)

Use at patio doors, fireplaces, exterior doors

various wood species available




SOLID REDUCER

(900mm, 1800mm or 2700mm with fixing bar)

Equalises the level between two different height flooring surfaces e.g. wood to vinyl

various wood species available



SOLID STAIR NOSING (1000mm)

Use on stair edge between riser and tread .
various wood species available in two different formats.



SCOTIA

Mdf Scotia hardwood colours and white (2440mm)

Solid Wood Scotia various species (2400mm)

Covers the expansion gap between the floor and wall
available in mdf or solid hardwood, various wood species.



PIPE ROSES

Solid wood pipe roses

various wood species available



SOLID OAK SKIRTING

Reversible solid wood skirting is available in American White Oak unlacquered.

Skirting can be stained and varnished to suit your requirements.

Skirting size: 120mm x 20mm x 2400mm.



UNDERLAYS

TIMBERMATE EXCEL


Resilient Rubber Underlay

Suitable for General Contract and Domestic Use

Increased Sound and Heat Insulation

For Use Under Engineered and Solid Timber Floors

Excellent Moisture Resistance when used with Vapourstop sealing strip very heavy weight construction approximately 3.75mm thickness tested to BS5808 : 1991 suitable for solids and engineered.



Independently tested to produce a rating of 56 SONE. • Suitable for underfloor heating. • 3.60 mm gauge high density resilient rubber underlay. • Incorporates a Vapourstop barrier, eliminating the need for extra moisture protection such as polythene sheeting. • Barrier membrane is ten times more moisture resistant than standard Polythene. • Prevents overstraining of wood and laminate boards. • Provides an excellent sub-floor masking minor surface imperfections. • Simple, quick and easy to install. • 14.6m x 0.685m (10 m²) roll



FOAM

Cellular Foam 2-3mm thick mainly used underneath engineered and laminates.



ADHESIVES

Rewmar MS Polymer flexible wood flooring adhesive

Used for bonding solid and engineered directly to the subfloor. Especially useful when installing directly over concrete. Special properties allow contraction and expansion of the wood. Takes up minor differences in levels.

Easy to apply by trowel

Easy to clean during and after use. No more black hands

Good coverage (approx. 1kg/m²) using 6mm V Notched trowel*

Can be stored part used so there is virtually no waste

Quick grab (open working time approx 20 minutes)

Moisture curing with a High final bond strength

Permanently flexible Dissipates shear forces

Suitable for use with underfloor heating

Waterproof



Rewmar P600

Rewmar Flexible Wood Flooring Adhesive Gun Applied.



Rewmar P600 is a cost-effective, permanently flexible adhesive that can be used with or without acoustic underlay.

Good acoustic qualities.

For an enhanced sound insulating system use with the special acoustic mat.

Easily applied using the gun in tram lines.

no hazard labelling

Polyurethane Base

600 ml sausage to fit applicator gun



PVA D3

Waterproof wood glue.

Use with engineered boards when installing as a floating floor .

FLOOR CLEANER

Bona Care Floor Cleaner System

Complete floor cleaning kit for wooden and cork floors



- Revolutionary microfibre threads attracting and absorbing dirt and microparticles
- Absorbs spill and removes tough stains

INCLUDES:

- Specially designed Bona Care mop with three-piece handle
- Bona Care Floor Cleaner spray bottle (1 litre)
- Washable Bona Care Cleaning Pad with dust absorbing microfibres

How to do?

- Cleans and polishes
- Microfibre dust absorption
- Use mop wet or dry


FLOOR TOOLS

Solid Wood Floor Fitting Kit

Solid Wood Floor Fitting Kit includes a Professional Pull Bar, Professional Push Block, 100 Spacers and Spatula, for the installation of solid wood flooring.



Tension Strap



Unika Tension Strap is specially designed to ensure several rows of floor panels at a time are tight and in position.

We recommend that you use 3-4 Tension Straps on a standard floor to guarantee no open joints.



mafkiidea

wood4floors.co.uk

Units 11 and 20 Malham Road Ind.Est.,
Malham Road, Forest Hill,
London SE23 1AH.

telephone

020 8699 7527

email: sales@wood4floors.co.uk



Opening hours

Monday to Friday 8.45am - 4.45pm Saturday 10.00am - 1.00pm